I. MECHANICAL SPECIFICATIONS :

Insulator :	Glass reinforced polyester, UL94V-0
Color:	Gray
Contact :	Phosphor Bronze, Tensile strength 95K PSI nom.
Contact Plating :	Per CA spec. #100003

II. ENVIRONMENTAL SPECIFICATIONS :

Temperature Rating :	-55°C to +125°C

III. ELECTRICAL SPECIFICATIONS :

Current Rating :	1.0 AMP
Voltage Rating :	300 V rms
Dielectric Withstanding Voltage: (At sea Level)	500 V rms
Insulation Resistance:	>1000 Megohms

IV. Meets the requirements of the European Parliament and the Restriction of the use of certain hazardous substances in eletrical and electronic equipment. (RoHS)

UNLESS OTHERWIES SPECIFIEDIMENSIONS ARE IN INCHES, TOLERANCES ARE :

FRACTIIONS ± DECIMALS .XX ± .XXX± ANGLES ±

APPROVALS		DATE
DRAWN	A. JOCHEN	11/13/84
CHECKED	J.mc Allister	11/13/84

THE INFORMATION AND DESIGN DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF CIRCUIT ASSEMBLY CORPOTATION. CIRCUIT ASSEMBLY CORPORATION RESERVES ALL PATENT, PROPRIETARY, DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO, AND TO ANY ARTICLE DISCLOSED HEREIN EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE FORGOING DOES NOT APPLY TO VENDOR PROPRIETARY RIGHTS.

REV	DESC.	DATE	INIT.
A	ECR 1975	11-13-84	A.J.
B	DO 7607	03-22-21	T.L.

CA **CIRCUIT ASSEMBLY CORP.**
6 AUTRY SUITE 150, IRVINE, CALIFORNIA 92618

SPECIFICATION - HEADER RECEPTACLE LOW PROFILE (HRLP) "RoHS"

SIZE	CODE IDENT NO.	DRAWING NO.	REV.
A	52072	100036	B

SCALE: NONE | DO NOT SCALE DRAWING | SHEET 1 OF 1