I. MECHANICAL SPECIFICATIONS:

Insulator:	Glass reinforced polyester UL-94V-0
Contact:	Phosphor Bronze
Plating:	Per CA Specification #100003
Contact Insertion Force:	16 oz. (454 grams) Max.
(using opposing pairs of contact)	8 oz. (225 grams) typ.
Contact Withdrawal Force:	2 oz. (57 grams) Min.
(using opposing pairs of contact)	
Normal Force: (per pair)	2 oz. (57 grams) nom.
Contact Retention:	7 lb. (3175 grams)/contact min.

II. ENVIRONMENTAL SPECIFICATIONS:

Temperature Rating:	-55°C to +125°C

III. ELECTRICAL SPECIFICATIONS:

Current Rating:	3 Amp
Voltage Rating: (at sea level)	600V DC
Dielectric Withstanding Voltage (at sea level)	650V AC rms Min.
Contact resistance:	< 10 milliohms typ.
	25 Milliohms Max.
Insulation Resistance:	> 5000 Megohms

IV. Connectors meet the preceding specification after 25 insertions with .062 thick steel blade.

V. Contact resistance was mearured using contacts selectively plated with .000020 inches of gold on contact area, mated with .062 thick print circuit board with contact fingers plated with .000020 inches of gold.

VI. Connector meets the class II durability criteria of EIA-IPC standard RE-406/IPC-C-405C which is 250 cycles at a rate of 100-300 cycles/hour.

VII. Meets the requirement of the European parliament and the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS).

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES, TOLERANCES ARE :

FRACTIONS ± DECIMALS .X ± .XX± ANGLES ±

THE INFORMATION AND DESIGN DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF CIRCUIT ASSEMBLY CORPOTATION. CIRCUIT ASSEMBLY CORPORATION RESERVES ALL PATENT, PROPRIETARY, DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO, AND TO ANY ARTICLE DISCLOSED HEREIN EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE FORGOING DOES NOT APPLY TO VENDOR PROPRIETARY RIGHTS.

APPROVALS		DATE
DRAWN	ART JOCHEN	07-22-83
CHECKED	John Mc Allister	07-22-83

REV	DESC.	DATE	INIT.
B	ECO 814	02-26-86	A.J.
C	DO 7593	12-10-2020	T.L.

CA **CIRCUIT ASSEMBLY CORP.**
6 AUTRY SUITE 150, IRVINE, CALIFORNIA 92618

SPECIFICATIONS - EC SERIES CONNECTOR, EDGE CARD

SIZE	CODE IDENT NO.	DRAWING NO.	REV.
A	52072	100031	C

SCALE: NONE | DO NOT SCALE DRAWING | SHEET 1 OF 1