

I. MECHANICAL SPECIFICATIONS

Insulator: Glass reinforced polyester UL-94V-0
 Contact: Phosphor bronze, tensile strength 95K psi nom.
 Plating: Per CA spec. 100003
 Color: Gray

II. ENVIRONMENTAL SPECIFICATIONS

Temp. Rating: -55 degree C to +125 degree C

III. ELECTRICAL SPECIFICATIONS

Current Rating: 1 Amp
 Voltage Rating: 300V rms
 Dielectric Withstanding Voltage: 500V rms (at sea level)
 Insulation Resistance: >1000 Megohms

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:

FRACTIONS DECIMALS ANGLES
 ± .XX ± ±
 .XXX ±

APPROVALS		DATE
DRAWN	<i>[Signature]</i>	11/13/84
CHECKED	<i>[Signature]</i>	11/13/84

CA **CIRCUIT ASSEMBLY CORP.**
 18 THOMAS ST., IRVINE, CALIFORNIA 92714-4194

REV	ECO	INIT	DATE
A	ECR JAL	MEG	11/13/84

SPECIFICATION - HEADER RECEPTACLE LOW PROFILE
 (HRLP)

SIZE A	CODE IDENT NO. 52072	DRAWING NO. 100036	REV. A
SCALE		DO NOT SCALE DRAWING	SHEET 1 OF 1