

**I. MECHANICAL SPECIFICATIONS :**

Insulator : Glass reinforced polyester, UL94V-0  
 Contact : Phosphor Bronze  
 Contact Plating : Contact Area : 12 microinches Gold  
 I.D. Area : 100 microinches Tin  
 Underplate : 75 microinches Nickel  
 Wire Size : 30 AWG 7/38 stranded  
 Contact Insertion Force : 3.17 oz ( 90g, 0.88N) Typical  
 4.23 oz (120g, 1.18N) Maximum  
 Contact Extraction Force : 2.82 oz ( 80g, 0.78N) Typical  
 2.12 oz ( 60g, 0.60N) Minimum

**II. ENVIRONMENTAL SPECIFICATIONS :**

Temperature Rating : -20°C to +105°C


**III. ELECTRICAL SPECIFICATIONS :**

Current Rating : 0.5 AMP  
 Dielectric  
 Withstanding Voltage : 500 VAC for 1 minute  
 Contact Resistance : 20 milliohms Maximum  
 measured through insulation displacement  
 portion and mating connector  
 Insulation Resistance : > 1000 Megohms

IV. Connectors meet or exceed the preceding specifications after 25 insertions with .028 wide X .020 thick blade.

**V. RECOGNITION :**

Underwriters Laboratories Inc. Component Recognition Program :  
 U.L file number E95981

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES, TOLERANCES ARE :	APPROVALS		DATE		 <b>CIRCUIT ASSEMBLY CORP.</b> 18 THOMAS ST., IRVINE, CALIFORNIA 92618-2777
	DRAWN R. PRITCHETT		11-5-91		
FRACTIONS    DECIMALS    ANGLES ±                    .XX ±                    ± .XXX ±	CHECKED A. JOCHEN		11-5-91		SPECIFICATION - NANOFLEX INSULATION DISPLACEMENT SOCKET CA-NFS
THE INFORMATION AND DESIGN DISCLOSED HEREIN WAS ORIGINATED BY AND IS THE PROPERTY OF CIRCUIT ASSEMBLY CORPORATION. CIRCUIT ASSEMBLY CORPORATION RESERVES ALL PATENT, PROPRIETARY, DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO, AND TO ANY ARTICLE DISCLOSED HEREIN EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE FORGOING DOES NOT APPLY TO VENDOR PROPRIETARY RIGHTS.	REV	DESC.	DATE	INIT.	
	A	ECR 1975	11-5-91	A.J.	
	B	DO 4983	9-17-02	A.J.	
	C	DO 6868	7-20-09	A.J.	
	SIZE	CODE IDENT NO.	DRAWING NO.	REV.	
	A	52072	100178	C	
	SCALE: NONE	DO NOT SCALE DRAWING	SHEET 1 OF 1		